

## **Reciprocating Saw XGT**

# JR001GZ



### **Product Description**

40V MAX XGT • 0 - 3 000 min<sup>-1</sup> • 32 mm

#### Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 – 3 000 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included

#### **Product Features**

- Toolless blade change and shoe adjustment
- Compact and ergonomic design
- Brushless maintenance-free and long-life motor
- Wide hanging hook, eg for scaffolding
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Battery protection system automatically shuts off power when the battery level is low

#### Barcode

88381893237

Product Specifications	
Vibration Level (3 axes), Cutting Wood	19,5 m/s <sup>2</sup>
Tool weight with battery (EPTA)	4,2 - 4,8 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	40 V
Brushless Motor	YES
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	85 dB(A)
Vibration Level (3 axes), Cutting Chipboard	18 m/s <sup>2</sup>
Length of Stroke	32 mm
Product Dimensions (L x W x H):	472 x 88 x 239 mm
Strokes per Minute (SPM)	0 - 2300 / 3000 min <sup>-1</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
System	XGT 40Vmax/80V max
Vibration Level (3 axes)	18,0 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	96 dB(A)
Product net weight (new)	3,5 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	130 mm
Tool Category	Sawing

## Standard Equipment

 $\odot$  Sold without Battery or Charger

More info

https://makita.ae/product/reciprocating-saw-xgt-jr001gz/