

## Reciprocating Saw XGT JR001GZ



### Product Description

40V MAX XGT • 0 - 3 000 min<sup>-1</sup> • 32 mm

#### Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 - 3 000 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included

### Product Features

- ⊙ Toolless blade change and shoe adjustment
- ⊙ Compact and ergonomic design
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Wide hanging hook, eg for scaffolding
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381893237

### Product Specifications

<b>Vibration Level (3 axes), Cutting Wood</b>	19,5 m/s <sup>2</sup>
<b>Tool weight with battery (EPTA)</b>	4,2 - 4,8 kg
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Max. Cutting Capacity in Wood (90°)</b>	255 mm
<b>Sound Pressure Level</b>	85 dB(A)
<b>Vibration Level (3 axes), Cutting Chipboard</b>	18 m/s <sup>2</sup>
<b>Length of Stroke</b>	32 mm
<b>Product Dimensions (L x W x H):</b>	472 x 88 x 239 mm
<b>Strokes per Minute (SPM)</b>	0 - 2300 / 3000 min <sup>-1</sup>
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Vibration Level (3 axes)</b>	18,0 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	96 dB(A)
<b>Product net weight (new)</b>	3,5 kg
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Cutting Capacity in Steel Pipe</b>	130 mm
<b>Tool Category</b>	Sawing

---

## Standard Equipment

- ⦿ Sold without Battery or Charger

## More info

<https://makita.ae/product/reciprocating-saw-xgt-jr001gz/>