

Rotary hammer HR2630X7



Product Description

800 W • SDS-PLUS • 26 mm • 2,4 J

Rotary Hammer for SDS-PLUS bits.

Powerful 800 W motor delivers 2.4 J of impact energy to handle the most demanding applications. Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection. Forward/reverse lever position of the switch allows brushes to be positioned so that the drill maintains same speed and torque in forward and reverse.

Product Features

- ⦿ The rubber coating on the handle ensures a firm working grip

Barcode

88381811385

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	68 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	15,0 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-18 mm
Sound Pressure Level	91 dB(A)
Power Supply Cord	4,0 m
Impact Energy	2,4 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	9,5 m/s ²
Product Dimensions (L x W x H):	361 x 77 x 209 mm
Impacts per Minute (IPM)	0 - 4600 min ⁻¹
Sound Power Level (L_{WA})	102 dB(A)
Weight Without Cable (EPTA)	2,8 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1200 min ⁻¹

More info

<https://makita.ae/product/rotary-hammer-hr2630x7/>