

Rotary Hammer

HR3011FCWJ



Product Description

1050 W • SDS-Plus • 30 mm • 3,6 J

Professional three-mode rotary hammer

Powerful rotary hammer for SDS-Plus blades with unique AVT anti-vibration system. The machine can be drilled without impact or with impact and has a spike function. The motor power is 1050 W and the speed is adjustable from 0-840min⁻¹. The device achieves a 3.6J impact force. The maximum capacity for drilling into concrete is 30 mm.

Product Features

- ⊙ High performance SDS-PLUS drill hammer; concrete max. 30 mm.
- ⊙ Impact drilling, non-impact drilling and spike function
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ LED light illuminates the work site
- ⊙ AVT (Anti-Vibration Technology) ensures extra-low vibration performance

Barcode

88381896726

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	80 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	10,8 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-16 mm
Sound Pressure Level	90 dB(A)
Power Supply Cord	2,5 m
Impact Energy	3,9 J
Continuous Input Power	1050 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	9,7 m/s ²
Product Dimensions (L x W x H):	369 x 98 x 242 mm
Impacts per Minute (IPM)	0 - 4500 min ⁻¹
Sound Power Level (L _{WA})	101 dB(A)
Weight Without Cable (EPTA)	4,8 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	30 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling

No load speed

0 - 840 min⁻¹

More info

<https://makita.ae/product/rotary-hammer-hr3011fcwj/>