



## Rotary Hammer HR3012FCWJ



### Product Description

1050 W • SDS-Plus • 30 mm • 3,6 J

#### Professional three-mode rotary hammer with quick change drill chuck

Powerful rotary hammer for SDS-Plus blades with unique AVT anti-vibration system. The machine can be drilled without impact or with impact and has a spike function. The motor power is 1050 W and the speed is adjustable from 0-840min-1. The device achieves a 3.6J impact force. The maximum capacity for drilling into concrete is 30 mm.

### Product Features

- ◎ High performance SDS-PLUS drill hammer; concrete max. 30 mm.
- ◎ Impact drilling, non-impact drilling and spike function
- ◎ The rubber coating on the handle ensures a firm working grip
- ◎ LED light illuminates the work site
- ◎ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ◎ Quick-change chuck for quick changeover to wood and metal drill bits.

### Barcode

88381896788

### Product Specifications

<b>Drilling diameter with TCT core bit</b>	80 mm
<b>Max. Drilling Diameter in Steel</b>	13 mm
<b>Max. Drilling Diameter in Wood</b>	32 mm
<b>Vibration Level (3 axes), Impact Drilling</b>	10,5 m/s <sup>2</sup>
<b>Optimum Drilling Diameter Range in Concrete</b>	8.0-16 mm
<b>Sound Pressure Level</b>	91 dB(A)
<b>Power Supply Cord</b>	2,5 m
<b>Impact Energy</b>	3,9 J
<b>Continuous Input Power</b>	1050 W
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Vibration: Chiselling</b>	8,2 m/s <sup>2</sup>
<b>Product Dimensions (L x W x H):</b>	386 x 98 x 242 mm
<b>Impacts per Minute (IPM)</b>	0 - 4500 min <sup>-1</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	102 dB(A)
<b>Weight Without Cable (EPTA)</b>	4,8 kg
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Drilling Diameter in Concrete</b>	30 mm
<b>Adapted for SDS-PLUS bits</b>	1
<b>Tool Category</b>	Hammer Drilling and Chiseling

**No load speed**

0 - 840 min<sup>-1</sup>

More info

<https://makita.ae/product/rotary-hammer-hr3012fcwj/>