

# Rotary Hammer HR4001C



## Product Description

1 100 W • SDS-Max • 40 mm • 6,8 J

### Rotary Hammer with high drilling power.

Rotary hammer for SDS-MAX blades with a powerful 1,100W motor.  
2 functions: impact drilling and picking function. Drilling power for concrete 40 mm.

## Product Features

- ⦿ Electronic speed control
- ⦿ Variable speed trigger allows operator to adjust speed based on materials or application
- ⦿ One-touch sliding chuck for easy bit installation and removal
- ⦿ 2-mode switch for “hammering only” or “hammering with rotation”
- ⦿ Double insulated
- ⦿ Soft start for smooth start-ups

## Barcode

88381066297

## Product Specifications

Plastic Carrying Case	1
Drilling diameter with TCT core bit	105 mm
Vibration Level (3 axes), Impact Drilling	12,5 m/s <sup>2</sup>
Optimum Drilling Diameter Range in Concrete	16-30 mm
Sound Pressure Level	92 dB(A)
Power Supply Cord	5,0 m
Vibration: Chiselling	10,5 m/s <sup>2</sup>
Product Dimensions (L x W x H):	468 x 106 x 261 mm
Impact Energy	6,8 J
Continuous Input Power	1100 W
Vibration Uncertainty (K Factor)	2,0 m/s <sup>2</sup>
Impacts per Minute (IPM)	1350 - 2750 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	103 dB(A)
Weight Without Cable (EPTA)	6,3 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	40 mm
Vibration Level (3 axes), Chiselling with D-type Side Handle	10,0 m/s <sup>2</sup>
Tool Category	Hammer Drilling and Chiseling
Adapted for SDS-MAX bits	1
No load speed	235 - 480 min <sup>-1</sup>

More info

<https://makita.ae/product/rotary-hammer-hr4001c/>