

Rotary Hammer HR4030C



Product Description

1 100 W • 40 mm • 9,2 J

Efficient rotary hammer for heavy work

An efficient 1 100 W rotary hammer with masonry drilling capacity of 40 mm and impact energy of 9,2 J. This tool is an ideal choice for renovation and building work. Aluminum housing provides high quality and the torque limiter brings safety to working.

Product Features

- ◎ Built-in torque limiting clutch disengages if bit jams
- ◎ Variable speed control dial enables user to match the speed to the application
- ◎ Soft start for smooth start-ups
- ◎ Rubberized soft grip for more comfort and control
- ◎ Double insulated

Barcode

88381079730

Product Specifications

Plastic Carrying Case	1
Drilling diameter with TCT core bit	105 mm
Optimum Drilling Diameter Range in Concrete	16-30 mm
Sound Pressure Level	91 dB(A)
Power Supply Cord	5,0 m
Product Dimensions (L x W x H):	413 x 107 x 247 mm
Impact Energy	9,2 J
Continuous Input Power	1100 W
Impacts per Minute (IPM)	1450 - 2900 min ⁻¹
Vibration Level (3 axes)	8,5 m/s ²
Sound Power Level (L_{WA})	102 dB(A)
Weight Without Cable (EPTA)	6,2 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	40 mm
Tool Category	Hammer Drilling and Chiseling
No load speed	250 - 500 min ⁻¹

More info

<https://makita.ae/product/rotary-hammer-hr4030c/>