

Rotary Hammer HR4501C



Product Description

1 350 W • SDS-Max • 45 mm • 12.5 J

Powerful dual-action combi hammer for heavy-duty use

Efficient 1 350 W combi hammer for SDS-MAX blades. Masonry drilling capacity of 45 mm and impact energy of 12,5 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.

Product Features

- ⊙ Kontrollleuchte meldet Betriebsbereitschaft und Kohlebürstenverschleiß
- ⊙ Dust-protected tool holder
- ⊙ Torque limiting clutch engineered to minimize gear damage by automatically disengaging gears if the bit binds

Barcode

88381084970

Product Specifications

| | |
|---|-------------------------------|
| Plastic Carrying Case | 1 |
| Drilling diameter with TCT core bit | 125 mm |
| Vibration Level (3 axes), Impact Drilling | 14,3 m/s ² |
| Optimum Drilling Diameter Range in Concrete | 20-35 mm |
| Sound Pressure Level | 94 dB(A) |
| Power Supply Cord | 5,0 m |
| Vibration: Chiselling | 9,9 m/s ² |
| Product Dimensions (L x W x H): | 458 x 121 x 288 mm |
| Continuous Input Power | 1350 W |
| Impact Energy | 10,1 J |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Impacts per Minute (IPM) | 1250 - 2750 min ⁻¹ |
| Sound Power Level (L _{WA}) | 105 dB(A) |
| Weight Without Cable (EPTA) | 7,8 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 45 mm |
| Tool Category | Hammer Drilling and Chiseling |
| Adapted for SDS-MAX bits | 1 |
| No load speed | 130 - 280 min ⁻¹ |

More info

<https://makita.ae/product/rotary-hammer-hr4501c/>