

# Rotary Hammer

## HR4511C



### Product Description

1 350 W • SDS-Max • 45 mm • 12.5 J

#### Powerful dual-action combi hammer with anti-vibration technology for heavy-duty use

An efficient 1 350 W combi hammer with a unique AVT anti-vibration system for SDS-MAX blades. Masonry drilling capacity of 45 mm and impact energy of 12,5 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.

### Product Features

- ⦿ AVT (Anti-Vibration Technology) ensures extra-low vibration performance

### Barcode

88381084956

### Product Specifications

Plastic Carrying Case	1
Drilling diameter with TCT core bit	125 mm
Vibration Level (3 axes), Impact Drilling	8,3 m/s <sup>2</sup>
Optimum Drilling Diameter Range in Concrete	20-35 mm
Sound Pressure Level	92 dB(A)
Power Supply Cord	5,0 m
Vibration: Chiselling	7,1 m/s <sup>2</sup>
Product Dimensions (L x W x H):	458 x 136 x 288 mm
Continuous Input Power	1350 W
Impact Energy	9,4 J
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Impacts per Minute (IPM)	1250 - 2750 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	103 dB(A)
Weight Without Cable (EPTA)	8,5 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	45 mm
Tool Category	Hammer Drilling and Chiseling
Adapted for SDS-MAX bits	1
No load speed	130 - 280 min <sup>-1</sup>

### More info

<https://makita.ae/product/rotary-hammer-hr4511c/>