

Rotary Hammer

HR5202C



Product Description

1 510 W • SDS-Max • 52 mm • 21J

Dual-action combi hammer for demanding professional use

Efficient 1 510 W combi hammer for SDS-MAX blades. Masonry drilling capacity of 52 mm and impact energy of 21 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.

Product Specifications

Plastic Carrying Case	1
Drilling diameter with TCT core bit	160 mm
Vibration Level (3 axes), Impact Drilling	15,7 m/s ²
Optimum Drilling Diameter Range in Concrete	25-40 mm
Sound Pressure Level	99 dB(A)
Power Supply Cord	4,0 m
Product Dimensions (L x W x H):	599 x 134 x 287 mm
Continuous Input Power	1510 W
Impact Energy	19,1 J
Vibration Uncertainty (K Factor)	2,0 m/s ²
Impacts per Minute (IPM)	1100 - 2250 min ⁻¹
Sound Power Level (L _{WA})	110 dB(A)
Weight Without Cable (EPTA)	10,9 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	52 mm
Tool Category	Hammer Drilling and Chiseling
Adapted for SDS-MAX bits	1
No load speed	150 - 310 min ⁻¹

More info

<https://makita.ae/product/rotary-hammer-hr5202c/>