

Rotary Hammer LXT

DHR171Z



Product Description

18V LXT • SDS-PLUS • 17 mm • 1,2 J

Compact, brushless tool for impact and unstressed drilling

A light, short-framed rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling. Speed can be adjusted between 0 and 680 min⁻¹. Impact energy of 1,2 J and max. drilling capacity of 17 mm in concrete. Tool only, battery and charger not included.

Product Features

- ⦿ Brushless maintenance-free and long-life motor
- ⦿ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381848503

Product Specifications

| | |
|---|-------------------------------|
| Max. Drilling Diameter in Steel | 10 mm |
| Max. Drilling Diameter in Wood | 13 mm |
| Vibration Level (3 axes), Impact Drilling | 11,2 m/s ² |
| Optimum Drilling Diameter Range in Concrete | 5,-8 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Tool weight with battery (EPTA) | 2,1 - 2,8 kg |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 90 dB(A) |
| Product Dimensions (L x W x H): | 273 x 86 x 211 mm |
| Impacts per Minute (IPM) | 0 - 4800 min ⁻¹ |
| Sound Power Level (L _{WA}) | 101 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 1,5 kg |
| Impact Energy | 1,2 J |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Hammer Drilling and Chiseling |
| Adapted for SDS-PLUS bits | 1 |
| Electronic brake | 1 |
| Max. Drilling Diameter in Concrete | 17 mm |
| Max Output Power | 480 W |
| No load speed | 0 - 680 min ⁻¹ |

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/rotary-hammer-lxt-dhr171z/>