

Rotary hammer XGT

HR005GZ01



Product Description

40V MAX XGT • SDS-PLUS • 40 mm • 8,0 J

Two-mode, anti-vibration rotary hammer for professionals

An efficient tool for SDS-MAX bits with AVT (anti-vibration technology) 40V max XGT batteries provide a high voltage. For impact and unstressed drilling and chipping. Speed range of 0 – 500 min⁻¹. Impact energy of 8.0 J, max. Capacity of 40 mm in concrete.

Product Specifications

Plastic Carrying Case	1
Drilling diameter with TCT core bit	105 mm
Tool weight with battery (EPTA)	7,4 - 8,8 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Impact Drilling	4,6 m/s ²
Optimum Drilling Diameter Range in Concrete	16-30 mm
Battery Voltage	40 V
Brushless Motor	YES
Sound Pressure Level	90 dB(A)
Impact Energy	8,0 J
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	3,7 m/s ²
Product Dimensions (L x W x H):	500 x 115 x 286 mm
Impacts per Minute (IPM)	1450 - 2900 min ⁻¹
System	XGT 40Vmax/80V max
Sound Power Level (L _{WA})	101 dB(A)
Product net weight (new)	6,3 kg
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	40 mm
Tool Category	Hammer Drilling and Chiseling
Electronic brake	1
AWS FUNCTION	YES
Adapted for SDS-MAX bits	1
No load speed	250 - 500 min ⁻¹

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/rotary-hammer-xgt-hr005gz01/>