

Rotary hammer XGT

HR006GZ



Product Description

80V MAX (40Vx2) XGT • SDS-MAX • 52 mm • 21.4 J

HR006G is an SDS-MAX cordless rotary hammer powered by two 40Vmax XGT Li-Ion batteries in series

With the twin battery system, the tool achieves the 80v max power. Combination of XGT system with powerful brushless motor provides high impact energy of 21.4J and delivers higher drilling efficiency.

Product Features

- ⦿ Active Feedback sensing Technology (AFT) turns the motor off if bit rotation is suddenly forced to stop
- ⦿ Anti-Vibration Technology (AVT) is a synchronized, three-component system that more effectively reduces vibration
- ⦿ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- ⦿ Twin LED lights with preglow and afterglow functions for better illumination and more accurate work
- ⦿ eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- ⦿ Depth gauge for increased drilling consistency
- ⦿ Torque limiting clutch engineered to minimize gear damage by automatically disengaging gears if the bit binds
- ⦿ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381739344

Product Specifications

| | |
|---|-------------------------------|
| Plastic Carrying Case | 1 |
| Drilling diameter with TCT core bit | 52 mm |
| Tool weight with battery (EPTA) | 12,9 - 14,3 kg |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Impact Drilling | 8,2 m/s ² |
| Optimum Drilling Diameter Range in Concrete | 25-40 mm |
| Battery Voltage | 2 x 40 V |
| Brushless Motor | YES |
| Sound Pressure Level | 98 dB(A) |
| Impact Energy | 21,4 J |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Vibration: Chiselling | 7,2 m/s ² |
| Product Dimensions (L x W x H): | 610 x 140 x 337 mm |
| Impacts per Minute (IPM) | 1100 - 2250 min ⁻¹ |
| System | XGT 40Vmax/80V max |
| Sound Power Level (L _{WA}) | 109 dB(A) |

| | |
|------------------------------------|-------------------------------|
| Product net weight (new) | 11,1 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 52 mm |
| Tool Category | Hammer Drilling and Chiseling |
| Electronic brake | 1 |
| AWS FUNCTION | YES |
| Adapted for SDS-MAX bits | 1 |
| No load speed | 150 - 310 min ⁻¹ |

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/rotary-hammer-xgt-hr006gz/>