

Slide Compound Miter Saw

LS1019L



Product Description

1 510 W • 260 mm • 3 200 min⁻¹

Efficient and accurate saw for high-capacity applications

An accurate high-capacity saw with a 1 510 W motor for building and other worksites. The dual slide system reduces the need for space, enabling the machine to be placed by a wall. The bevel lock is located at the front of the saw. Excellent dust removal function.

Product Features

- ⊙ superior capacity
- ⊙ outstanding dust extraction
- ⊙ can be placed all the way to the wall due to new construction

Barcode

88381843997

Product Specifications

Bore Size (Arbor Diameter)	30 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	91 x 197 / 68 x 218 mm
Capacity 90°	91 x 279 / 68 x 310 mm
Capacity 45° left (Miter 0°, Bevel L 45°)	58 x 279 / 42 x 310 mm
Sound Pressure Level	91 dB(A)
Max. Bevel Range (Left)	48 / 48 °
Laser Class	2M
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	805 x 644 x 660 mm
Continuous Input Power	1510 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L_{WA})	101 dB(A)
Weight Without Cable (EPTA)	26,3 kg
Noise Uncertainty (K Factor)	3 dB(A)
Blade Diameter	260 mm
Tool Category	Sawing
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	43 x 279 / 29 x 305 mm
Max. Mitre Range (Left)	60 / 60 °
No load speed	3200 min ⁻¹

More info

<https://makita.ae/product/slide-compound-miter-saw-ls1019/>