

Slide Compound Miter Saw LXT

DLS111ZU



Product Description

36V (18Vx2) LXT • 260 mm • 4 400 min⁻¹

Efficient brushless cordless saw with a AWS remote start for dust extraction for demanding use

An extremely powerful and quick high-capacity saw with a dual slide system for cutting large pieces. Its two 18V LXT batteries and brushless motor achieve 18V+18V capacity. Its cutting speed is comparable to electric mitre saws. Battery and charger not included.

Product Features

- Battery protection system automatically shuts off power when the battery level is low
- Brushless maintenance-free and long-life motor
- Can be used cordlessly against AWS vacuum cleaner.

Barcode

88381851268

- I		100	
Prod	llict Si	pecificat	tions

Bore Size (Arbor Diameter) 30 mm Capacity 45° (Miter R/L 45°, Bevel 0°) 91 x 197 / 68 x 218 mm Capacity 90° 91 x 279 / 68 x 310 mm Capacity 45° left (Miter 0°, Bevel L 45°) 58 x 279 / 42 x 310 mm Tool weight with battery (EPTA) 26,6 - 27,3 kg Brushless Motor YES Battery Voltage 2 x 18 V Laser Class 2M Max. Bevel Range (Left) 48 / 48 ° Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (L _{WA}) 102 dB(A) Voltage LXT 1 System LXT 18V/36V Product net weight (new) 25 1 kg	·	
Capacity 90° 91 x 279 / 68 x 310 mm Capacity 45° left (Miter 0°, Bevel L 45°) 58 x 279 / 42 x 310 mm Tool weight with battery (EPTA) 26,6 - 27,3 kg Brushless Motor YES Battery Voltage 2 x 18 V Laser Class 2M Max. Bevel Range (Left) 48 / 48 ° Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (L _{WA}) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Bore Size (Arbor Diameter)	30 mm
Capacity 45° left (Miter 0°, Bevel L 45°) 58 x 279 / 42 x 310 mm Tool weight with battery (EPTA) 26,6 - 27,3 kg Brushless Motor YES Battery Voltage 2 x 18 V Laser Class 2M Max. Bevel Range (Left) 48 / 48 ° Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (L _{WA}) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Capacity 45° (Miter R/L 45°, Bevel 0°)	91 x 197 / 68 x 218 mm
Tool weight with battery (EPTA) $26,6 - 27,3 \text{ kg}$ Brushless MotorYESBattery Voltage $2 \times 18 \text{ V}$ Laser Class $2M$ Max. Bevel Range (Left) $48 / 48 \degree$ Sound Pressure Level $92 \text{ dB}(A)$ Product Dimensions (L x W x H): $805 \times 644 \times 660 \text{ mm}$ Vibration Level (3 axes)≤ $2,5 \text{ m/s}^2$ Sound Power Level (LwA) $102 \text{ dB}(A)$ Voltage LXT 1 SystemLXT $18V/36V$	Capacity 90°	91 x 279 / 68 x 310 mm
Brushless MotorYESBattery Voltage $2 \times 18 \text{ V}$ Laser Class $2M$ Max. Bevel Range (Left) $48 / 48 \degree$ Sound Pressure Level $92 \text{ dB}(A)$ Product Dimensions (L x W x H): $805 \times 644 \times 660 \text{ mm}$ Vibration Level (3 axes) $\leq 2,5 \text{ m/s}^2$ Sound Power Level (L _{WA}) $102 \text{ dB}(A)$ Voltage LXT1SystemLXT $18V/36V$	Capacity 45° left (Miter 0°, Bevel L 45°)	58 x 279 / 42 x 310 mm
Battery Voltage 2 x 18 V Laser Class 2M Max. Bevel Range (Left) 48 / 48 ° Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (LwA) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Tool weight with battery (EPTA)	26,6 - 27,3 kg
Laser Class 2M Max. Bevel Range (Left) 48 / 48 º Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (LwA) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Brushless Motor	YES
Max. Bevel Range (Left) 48 / 48 º Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (LwA) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Battery Voltage	2 x 18 V
Sound Pressure Level 92 dB(A) Product Dimensions (L x W x H): 805 x 644 x 660 mm Vibration Level (3 axes) ≤ 2,5 m/s² Sound Power Level (LwA) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Laser Class	2M
Product Dimensions (L x W x H): $805 \times 644 \times 660 \text{ mm}$ Vibration Level (3 axes)≤ 2,5 m/s²Sound Power Level (L _{WA}) $102 \text{ dB}(A)$ Voltage LXT1SystemLXT $18V/36V$	Max. Bevel Range (Left)	48 / 48 º
Vibration Level (3 axes) $\leq 2,5 \text{ m/s}^2$ Sound Power Level (LwA) $102 \text{ dB}(A)$ Voltage LXT1SystemLXT $18V/36V$	Sound Pressure Level	92 dB(A)
Sound Power Level (LwA) 102 dB(A) Voltage LXT 1 System LXT 18V/36V	Product Dimensions (L x W x H):	805 x 644 x 660 mm
Voltage LXT 1 System LXT 18V/36V	Vibration Level (3 axes)	≤ 2,5 m/s ²
System LXT 18V/36V	Sound Power Level (L _{WA})	102 dB(A)
•	Voltage LXT	1
Product net weight (new) 25.1 kg	System	LXT 18V/36V
25,1 kg	Product net weight (new)	25,1 kg
Vibration Uncertainty (K Factor) 1,5 m/s ²	Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor) 3 dB(A)	Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out 35/40 mm	Vacuum cleaner connection Ø in / out	35/40 mm
Tool Category Sawing	Tool Category	Sawing
Blade Diameter 260 mm	Blade Diameter	260 mm

No load speed	4400 min ⁻¹
AWS FUNCTION	YES
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	43 x 279 / 29 x 305 mm
Max. Mitre Range (Left)	60 / 60 º

Standard Equipment

• With Wireless Unit and Sold without Battery or Charger

More info

https://makita.ae/product/slide-compound-miter-saw-lxt-dls111zu/