

Slide Compound Miter Saw LXT

DLS713Z



Product Description

18V LXT • 190 mm • 2 200 min⁻¹

A light and powerful slide compound saw for builders

A cordless slide compound saw for cross and mitre cutting with a blade diameter of 190 mm. An ideal choice for construction and other demanding sectors. Four steel poles with four linear ball bearings ensure stable and accurate cutting. Tool only, battery and charger not included.

Product Features

- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ Body model - delivered without battery and charger.

Barcode

88381672764

Product Specifications

| | |
|--|------------------------|
| Bore Size (Arbor Diameter) | 20 mm |
| Capacity 45° (Miter R/L 45°, Bevel 0°) | 52 x 212 mm |
| Capacity 90° | 52 x 300 mm |
| Capacity 45° left (Miter 0°, Bevel L 45°) | 25 x 300 mm |
| Tool weight with battery (EPTA) | 12,4 - 12,7 kg |
| Battery Voltage | 18 V |
| Max. Bevel Range (Left) | 45 / 5 ° |
| Sound Pressure Level | 88 dB(A) |
| Product Dimensions (L x W x H): | 655 x 430 x 454 mm |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Sound Power Level (L_{WA}) | 98 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 12,0 kg |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vacuum cleaner connection Ø in / out | 32/37 mm |
| Tool Category | Sawing |
| Blade Diameter | 190 mm |
| No load speed | 2200 min ⁻¹ |
| Max. Mitre Range (Left) | 47 / 57 ° |

Standard Equipment

- ⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/slide-compound-miter-saw-lxt-dls713z/>