

# Slide Compound Miter Saw LXT

## DLS714NZ



### Product Description

36V (18Vx2) LXT • 190 mm • 5 700 min<sup>-1</sup>

#### Efficient brushless cordless saw for demanding use

A quick and efficient saw with a dual slide system for cutting large pieces as well as skirting boards. The tool's two 18V LXT batteries and brushless motor achieve a 18V+18V capacity, providing cutting speed that is comparable to electric mitre saws. Battery and charger not included.

### Product Features

- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ Body model - delivered without battery and charger.
- ⊙ Brushless maintenance-free and long-life motor

### Barcode

88381877039

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	20 mm
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	52 x 212 mm
<b>Capacity 90°</b>	52 x 300 mm
<b>Capacity 45° left (Miter 0°, Bevel L 45°)</b>	40 x 300 mm
<b>Tool weight with battery (EPTA)</b>	14.4 - 14.7 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	2 x 18 V
<b>Max. Bevel Range (Left)</b>	45 / 5 °
<b>Sound Pressure Level</b>	88 dB(A)
<b>Product Dimensions (L x W x H):</b>	655 x 430 x 445 mm
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	97 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	13,4 kg
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Vacuum cleaner connection Ø in / out</b>	32/37 mm
<b>Tool Category</b>	Sawing
<b>Blade Diameter</b>	190 mm
<b>No load speed</b>	5700 min <sup>-1</sup>
<b>Max. Mitre Range (Left)</b>	47 / 57 °

## Standard Equipment

- ⦿ Sold without Battery or Charger

## More info

<https://makita.ae/product/slide-compound-miter-saw-lxt-dls714nz/>