

# Slide Compound Miter Saw XGT

## LS003GZ



### Product Description

40V MAX XGT • 305mm

#### **305mm Cordless Slide Compound Miter Saw Powered by 40V MAX Lithium-Ion Battery**

Precise cutting and user's comfort. Delivers high performance with 3,600 RPM for fast and smooth cutting (Sold without Battery and Charger)

### Product Features

- ⊙ High power delivered by 40Vmax BL motor enables to cut as fast as if you were using a corded slide compound miter saw
- ⊙ Vacuum cleaner activation switch for increased comfort
- ⊙ LED light with ink line aligning function
- ⊙ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- ⊙ Large turn base supports workpiece securely for increased stability
- ⊙ Integrated guide fences for increased rigidity and high cutting accuracy
- ⊙ Front knob for easy bevel angle adjustment
- ⊙ Holders are provided on both sides of the tool to hold long workpieces horizontally
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381746304

### Product Specifications

|  |                         |
|--|-------------------------|
| <b>Bore Size (Arbor Diameter)</b>                | 30 mm                   |
| <b>Tool weight with battery (EPTA)</b>           | 30,5 - 31,7 kg          |
| <b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>    | 107 x 255 / 92 x 268 mm |
| <b>Capacity 90°</b>                              | 107 x 363 / 92 x 382 mm |
| <b>Capacity 45° left (Miter 0°, Bevel L 45°)</b> | 71 x 363 / 61 x 382 mm  |
| <b>Battery Voltage</b>                           | 40 V                    |
| <b>Brushless Motor</b>                           | YES                     |
| <b>Sound Pressure Level</b>                      | 91 dB(A)                |
| <b>Max. Bevel Range (Left)</b>                   | 48 / 48 °               |
| <b>Product Dimensions (L x W x H):</b>           | 898 x 690 x 725 mm      |
| <b>Vibration Uncertainty (K Factor)</b>          | 1,5 m/s <sup>2</sup>    |
| <b>Product net weight (new)</b>                  | 28,9 kg                 |
| <b>System</b>                                    | XGT 40Vmax/80V max      |

|   |                        |
|---|------------------------|
| <b>Vibration Level (3 axes)</b>                         | ≤ 2,5 m/s <sup>2</sup> |
| <b>Sound Power Level (L<sub>WA</sub>)</b>               | 100 dB(A)              |
| <b>Voltage XGT</b>                                      | 1                      |
| <b>Noise Uncertainty (K Factor)</b>                     | 3 dB(A)                |
| <b>Vacuum cleaner connection Ø in / out</b>             | 35/40 mm               |
| <b>Blade Diameter</b>                                   | 305 mm                 |
| <b>Tool Category</b>                                    | Sawing                 |
| <b>AWS FUNCTION</b>                                     | YES                    |
| <b>Bevel capacity right 45° (Miter 0°, Bevel R 45°)</b> | 54 x 363 / 44 x 382 mm |
| <b>No load speed</b>                                    | 3600 min <sup>-1</sup> |
| <b>Max. Mitre Range (Left)</b>                          | 60 / 60 °              |

#### Standard Equipment

- ⊙ Sold without Battery or Charger

#### More info

<https://makita.ae/product/slide-compound-miter-saw-xgt-ls003gz/>