

# Slide Compound Miter Saw XGT

## LS003GZ



### Product Description

40V MAX XGT • 305mm

#### **305mm Cordless Slide Compound Miter Saw Powered by 40V MAX Lithium-Ion Battery**

Precise cutting and user's comfort. Delivers high performance with 3,600 RPM for fast and smooth cutting (Sold without Battery and Charger)

### Product Features

- ⊙ High power delivered by 40Vmax BL motor enables to cut as fast as if you were using a corded slide compound miter saw
- ⊙ Vacuum cleaner activation switch for increased comfort
- ⊙ LED light with ink line aligning function
- ⊙ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- ⊙ Large turn base supports workpiece securely for increased stability
- ⊙ Integrated guide fences for increased rigidity and high cutting accuracy
- ⊙ Front knob for easy bevel angle adjustment
- ⊙ Holders are provided on both sides of the tool to hold long workpieces horizontally
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381746304

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	30 mm
<b>Tool weight with battery (EPTA)</b>	30,5 - 31,7 kg
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	107 x 255 / 92 x 268 mm
<b>Capacity 90°</b>	107 x 363 / 92 x 382 mm
<b>Capacity 45° left (Miter 0°, Bevel L 45°)</b>	71 x 363 / 61 x 382 mm
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Sound Pressure Level</b>	91 dB(A)
<b>Max. Bevel Range (Left)</b>	48 / 48 °
<b>Product Dimensions (L x W x H):</b>	898 x 690 x 725 mm
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Product net weight (new)</b>	28,9 kg
<b>System</b>	XGT 40Vmax/80V max

<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	100 dB(A)
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Vacuum cleaner connection Ø in / out</b>	35/40 mm
<b>Blade Diameter</b>	305 mm
<b>Tool Category</b>	Sawing
<b>AWS FUNCTION</b>	YES
<b>Bevel capacity right 45° (Miter 0°, Bevel R 45°)</b>	54 x 363 / 44 x 382 mm
<b>No load speed</b>	3600 min <sup>-1</sup>
<b>Max. Mitre Range (Left)</b>	60 / 60 °

#### Standard Equipment

- ⊙ Sold without Battery or Charger

#### More info

<https://makita.ae/product/slide-compound-miter-saw-xgt-ls003gz/>