

Slide Compound Miter Saw XGT LS004GZ



Product Description

40V MAX XGT • 260mm

260mm Cordless Slide Compound Miter Saw Powered by 40V MAX Lithium-Ion Battery

Precise cutting and user's comfort. Delivers high performance with 3,600 RPM for fast and smooth cutting (Sold without battery and Charger)

Product Features

- ◎ Brushless maintenance-free and long-life motor
- ◎ High precision cutting
- ◎ Rail-forward design enables to be placed against a wall for maximizing work space
- ◎ Single sliding system enables smooth operation to produce superior cuts
- ◎ Large bevel lock lever; Easy to operate even if the machine is placed close to wall, because you need not reach for the rear of the machine to turn the lever
- ◎ Precision miter angle adjustment; Can be achieved simply by turning a knob on the turn base
- ◎ Extendable sub tables help stabilize long material cuts
- ◎ Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- ◎ Built-in fluorescent light illuminates cutting edge
- ◎ Front knob for easy bevel angle adjustment
- ◎ One-touch slide lock; Can be easily locked/unlocked by inserting/removing the lock pin
- ◎ Ergonomic rubberized D-handle design for better fit and added comfort
- ◎ Soft start feature for smooth start-ups
- ◎ Electric brake for maximum productivity and increased operator safety
- ◎ Battery protection circuit protects against overloading, over-discharging and over-heating
- ◎ Single sliding system enables smooth operation to produce superior cuts
- ◎ Extendable sub tables help stabilize long material cuts

Barcode

88381748544

Product Specifications

Bore Size (Arbor Diameter)	30 mm
Tool weight with battery (EPTA)	26,6 - 27,8 kg
Capacity 45° (Miter R/L 45°, Bevel 0°)	91 x 279 / 68 x 218 mm
Capacity 90°	91 x 279 / 68 x 310 mm

Capacity 45° left (Miter 0°, Bevel L 45°)	58 x 279 / 42 x 310 mm
Battery Voltage	40 V
Brushless Motor	YES
Sound Pressure Level	91 dB(A)
Max. Bevel Range (Left)	48 / 48 °
Product Dimensions (L x W x H):	805 x 644 x 660 mm
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product net weight (new)	25,1 kg
System	XGT 40Vmax/80V max
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L_{WA})	100 dB(A)
Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out	35/40 mm
Blade Diameter	260 mm
Tool Category	Sawing
AWS FUNCTION	YES
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	43 x 279 / 29 x 305 mm
Max. Mitre Range (Left)	60 / 60 °
No load speed	3600 min ⁻¹

Standard Equipment

◎ Sold without Battery or Charger

More info

<https://makita.ae/product/slide-compound-miter-saw-xgt-ls004gz/>