

## Slide Compound Saw LS0714



### Product Description

1 010 W • 190 mm • 6 000 min<sup>-1</sup>

#### Light and portable saw for builders

A slide compound saw for cross and mitre cutting with a 1 010 W motor and a blade with a diameter of 190 mm. An ideal choice for construction and other demanding sectors. Four steel poles with four linear ball bearings ensure stable and accurate cutting.

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	20 mm
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	52 x 212 mm
<b>Capacity 90°</b>	52 x 300 mm
<b>Capacity 45° left (Miter 0°, Bevel L 45°)</b>	40 x 300 mm
<b>Sound Pressure Level</b>	92 dB(A)
<b>Max. Bevel Range (Left)</b>	45 / 5 °
<b>Power Supply Cord</b>	2,5 m
<b>Product Dimensions (L x W x H):</b>	670 x 430 x 458 mm
<b>Continuous Input Power</b>	1010 W
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	101 dB(A)
<b>Weight Without Cable (EPTA)</b>	13,1 kg
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Vacuum cleaner connection Ø in / out</b>	32/37 mm
<b>Blade Diameter</b>	190 mm
<b>Tool Category</b>	Sawing
<b>No load speed</b>	6000 min <sup>-1</sup>
<b>Max. Mitre Range (Left)</b>	47 / 57 °

### More info

<https://makita.ae/product/slide-compound-saw-ls0714/>