

Slide Compound Saw LS0714



Product Description

1 010 W • 190 mm • 6 000 min⁻¹

Light and portable saw for builders

A slide compound saw for cross and mitre cutting with a 1 010 W motor and a blade with a diameter of 190 mm. An ideal choice for construction and other demanding sectors. Four steel poles with four linear ball bearings ensure stable and accurate cutting.

Product Specifications

Bore Size (Arbor Diameter)	20 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	52 x 212 mm
Capacity 90°	52 x 300 mm
Capacity 45° left (Miter 0°, Bevel L 45°)	40 x 300 mm
Sound Pressure Level	92 dB(A)
Max. Bevel Range (Left)	45 / 5 °
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	670 x 430 x 458 mm
Continuous Input Power	1010 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L_{WA})	101 dB(A)
Weight Without Cable (EPTA)	13,1 kg
Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out	32/37 mm
Blade Diameter	190 mm
Tool Category	Sawing
No load speed	6000 min ⁻¹
Max. Mitre Range (Left)	47 / 57 °

More info

<https://makita.ae/product/slide-compound-saw-ls0714/>