

### **Slide Compound Saw**

## **LS1018LN**



#### **Product Description**

1 430 W • 260 mm • 4 300 min<sup>-1</sup>

# Efficient and accurate saw with a laser for high-capacity applications

- Large Cutting Capacity in a Compact Design and Less Weight
- · Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large precision machined aluminum base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort, and easier operation

#### **Product Features**

- Large Cutting Capacity in a Compact Design and Less Weight
- Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large precision machined aluminum base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort and easier operation

#### Barcode

#### 88381868143

Product Specifications	
Bore Size (Arbor Diameter)	30 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	91 x 215 mm
Capacity 90°	91 x 310 mm
Capacity 45° left (Miter 0°, Bevel L 45°)	50 x 310 mm
Sound Pressure Level	92 dB(A)
Laser Class	2M
Max. Bevel Range (Left)	45 / 45 º
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	825 x 536 x 633 mm

Continuous Input Power	1430 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Vibration Level (3 axes)	≤ 2,5 m/s²
Sound Power Level (L <sub>wA</sub> )	102 dB(A)
Weight Without Cable (EPTA)	19,9 kg
Noise Uncertainty (K Factor)	3 dB(A)
Blade Diameter	260 mm
Tool Category	Sawing
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	31 x 310 mm
Max. Mitre Range (Left)	47 / 60 º
No load speed	4300 min <sup>-1</sup>

## More info

https://makita.ae/product/slide-compound-saw-ls1018ln/