

Slide Compound Saw LS1018LN



Product Description

1 430 W • 260 mm • 4 300 min⁻¹

Efficient and accurate saw with a laser for high-capacity applications

- Large Cutting Capacity in a Compact Design and Less Weight
- Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large precision machined aluminum base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort, and easier operation

Product Features

- ⊙ Large Cutting Capacity in a Compact Design and Less Weight
- ⊙ Less weight and compact design for job site portability
- ⊙ Soft start feature for smooth start-ups
- ⊙ Ergonomic rubberized D-handle design for better fit and added comfort
- ⊙ Large precision machined aluminum base supports material for more efficient cutting
- ⊙ Electric brake for maximum productivity
- ⊙ Dust bag for a cleaner work environment
- ⊙ See-through blade guard system for greater visibility of blade and line of cut
- ⊙ Oversized trigger switch for better fit, added comfort and easier operation

Barcode

88381868143

Product Specifications

| | |
|--|--------------------|
| Bore Size (Arbor Diameter) | 30 mm |
| Capacity 45° (Miter R/L 45°, Bevel 0°) | 91 x 215 mm |
| Capacity 90° | 91 x 310 mm |
| Capacity 45° left (Miter 0°, Bevel L 45°) | 50 x 310 mm |
| Sound Pressure Level | 92 dB(A) |
| Laser Class | 2M |
| Max. Bevel Range (Left) | 45 / 45 ° |
| Power Supply Cord | 2,5 m |
| Product Dimensions (L x W x H): | 825 x 536 x 633 mm |

| | |
|---|------------------------|
| Continuous Input Power | 1430 W |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Sound Power Level (L_{WA}) | 102 dB(A) |
| Weight Without Cable (EPTA) | 19,9 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Blade Diameter | 260 mm |
| Tool Category | Sawing |
| Bevel capacity right 45° (Miter 0°, Bevel R 45°) | 31 x 310 mm |
| Max. Mitre Range (Left) | 47 / 60 ° |
| No load speed | 4300 min ⁻¹ |

More info

<https://makita.ae/product/slide-compound-saw-ls1018ln/>