

## Slide Compound Saw

# LS1018LN



### Product Description

1 430 W • 260 mm • 4 300 min<sup>-1</sup>

#### Efficient and accurate saw with a laser for high-capacity applications

- Large Cutting Capacity in a Compact Design and Less Weight
- Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large precision machined aluminum base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort, and easier operation

### Product Features

- ⦿ Large Cutting Capacity in a Compact Design and Less Weight
- ⦿ Less weight and compact design for job site portability
- ⦿ Soft start feature for smooth start-ups
- ⦿ Ergonomic rubberized D-handle design for better fit and added comfort
- ⦿ Large precision machined aluminum base supports material for more efficient cutting
- ⦿ Electric brake for maximum productivity
- ⦿ Dust bag for a cleaner work environment
- ⦿ See-through blade guard system for greater visibility of blade and line of cut
- ⦿ Oversized trigger switch for better fit, added comfort and easier operation

### Barcode

88381868143

### Product Specifications

Bore Size (Arbor Diameter)	30 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	91 x 215 mm
Capacity 90°	91 x 310 mm
Capacity 45° left (Miter 0°, Bevel L 45°)	50 x 310 mm
Sound Pressure Level	92 dB(A)
Laser Class	2M
Max. Bevel Range (Left)	45 / 45 °
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	825 x 536 x 633 mm

<b>Continuous Input Power</b>	1430 W
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	102 dB(A)
<b>Weight Without Cable (EPTA)</b>	19,9 kg
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Blade Diameter</b>	260 mm
<b>Tool Category</b>	Sawing
<b>Bevel capacity right 45° (Miter 0°, Bevel R 45°)</b>	31 x 310 mm
<b>Max. Mitre Range (Left)</b>	47 / 60 °
<b>No load speed</b>	4300 min <sup>-1</sup>

More info

<https://makita.ae/product/slide-compound-saw-ls1018ln/>