

## Slide Compound Saw

# LS1018LN



### Product Description

1 430 W • 260 mm • 4 300 min<sup>-1</sup>

#### Efficient and accurate saw with a laser for high-capacity applications

- Large Cutting Capacity in a Compact Design and Less Weight
- Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large precision machined aluminum base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort, and easier operation

### Product Features

- ⦿ Large Cutting Capacity in a Compact Design and Less Weight
- ⦿ Less weight and compact design for job site portability
- ⦿ Soft start feature for smooth start-ups
- ⦿ Ergonomic rubberized D-handle design for better fit and added comfort
- ⦿ Large precision machined aluminum base supports material for more efficient cutting
- ⦿ Electric brake for maximum productivity
- ⦿ Dust bag for a cleaner work environment
- ⦿ See-through blade guard system for greater visibility of blade and line of cut
- ⦿ Oversized trigger switch for better fit, added comfort and easier operation

### Barcode

88381868143

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	30 mm
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	91 x 215 mm
<b>Capacity 90°</b>	91 x 310 mm
<b>Capacity 45° left (Miter 0°, Bevel L 45°)</b>	50 x 310 mm
<b>Sound Pressure Level</b>	92 dB(A)
<b>Laser Class</b>	2M
<b>Max. Bevel Range (Left)</b>	45 / 45 °
<b>Power Supply Cord</b>	2,5 m
<b>Product Dimensions (L x W x H):</b>	825 x 536 x 633 mm

Continuous Input Power	1430 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Vibration Level (3 axes)	≤ 2,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	102 dB(A)
Weight Without Cable (EPTA)	19,9 kg
Noise Uncertainty (K Factor)	3 dB(A)
Blade Diameter	260 mm
Tool Category	Sawing
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	31 x 310 mm
Max. Mitre Range (Left)	47 / 60 °
No load speed	4300 min <sup>-1</sup>

More info

<https://makita.ae/product/slide-compound-saw-ls1018ln/>