

Slide Compound Saw LS1219L



Product Description

1 800 W • 305 mm • 3 200 min⁻¹

Efficient high-capacity saw with a laser for quick and accurate cutting

An accurate high-capacity mitre saw with a 1 800 W motor for professional use. The dual slide system reduces the need for space, enabling the machine to be placed by a wall. The bevel lock is located at the front of the saw. Equipped with an excellent dust removal function and a built-in laser that indicates line-of-cut.

Product Specifications

Bore Size (Arbor Diameter)	30 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	107 x 255 / 92 x 268 mm
Capacity 90°	107 x 363 / 92 x 382 mm
Capacity 45° left (Miter 0°, Bevel L 45°)	71 x 363 / 61 x 382 mm
Sound Pressure Level	91 dB(A)
Max. Bevel Range (Left)	48 / 48 °
Laser Class	2M
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	898 x 664 x 725 mm
Continuous Input Power	1800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L _{WA})	100 dB(A)
Weight Without Cable (EPTA)	29,5 kg
Noise Uncertainty (K Factor)	3 dB(A)
Blade Diameter	305 mm
Tool Category	Sawing
Bevel capacity right 45° (Miter 0°, Bevel R 45°)	54 x 363 / 44 x 382 mm
No load speed	3200 min ⁻¹
Max. Mitre Range (Left)	60 / 60 °

More info

<https://makita.ae/product/slide-compound-saw-ls1219/>