

## Steel Rod Cutter LXT

# DSC251ZK



### Product Description

18V LXT • 10 - 25 mm • 2 200 min<sup>-1</sup>

#### Fast, nearly spark-free cutting of steel rods and rebars

A cutter designed for cutting steel rods and rebars. Max. cutting capacity of 25 mm, fine edge cutting (3,5 mm). A three-position removable side grip for added comfort. Tool only, battery and charger not included. Comes with case.

### Product Features

- ⊙ No dust, no sparks.
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381873543

### Product Specifications

|  |                        |
|--|------------------------|
| Plastic Carrying Case  | 1                      |
| Cutting Capacity Stainless Steel (up to 600N/mm <sup>2</sup> ) | 25 mm                  |
| Tool weight with battery (EPTA)                                | 3,9 - 4,0 kg           |
| Cutting Capacity Mild Steel (up to 400N/mm <sup>2</sup> )      | 25 mm                  |
| Brushless Motor  | YES                    |
| Battery Voltage  | 18 V                   |
| Sound Pressure Level   | 78 dB(A)               |
| Product Dimensions (L x W x H):                                | 471 x 137 x 139 mm     |
| Vibration Level (3 axes)                                       | ≤ 2,5 m/s <sup>2</sup> |
| Voltage LXT  | 1                      |
| System   | LXT 18V/36V            |
| Product net weight (new)                                       | 3,3 kg                 |
| Vibration Uncertainty (K Factor)                               | 1,5 m/s <sup>2</sup>   |
| Noise Uncertainty (K Factor)                                   | 3 dB(A)                |
| Tool Category  | Cutting                |
| Blade Diameter   | 110 mm                 |
| No load speed  | 2200 min <sup>-1</sup> |

### Standard Equipment

- ⊙ With Carry Case and Sold without Battery or Charger

### More info

<https://makita.ae/product/steel-rod-cutter-lxt-dsc251zk/>