

## Tower Light / Work Light LXT

# DML814Z



### Product Description

• 18V LXT • 1,250 LX • 12 LED

#### Two lighting modes Spot lighting / Area lighting

3 brightness settings: 3,000 lumens on high mode. Two lighting modes: Spot lighting / Area lighting. Telescopic light mast enables lighting at a height up to 2.2m. Highly stable tripod base, foldable into a compact size for simple storage and transport. Tool only, battery and charger not included.

### Product Features

- ⊙ 3 brightness settings (HI / MED / LO)
- ⊙ The lighting area can be adjusted by turning the individual lamp units
- ⊙ Adjustable height
- ⊙ IP55 certified dust and water resistance
- ⊙ Padlocked battery cover for increased security
- ⊙ Battery capacity warning function automatically notifies the user about reduction in battery capacity with the decrease of illuminance
- ⊙ Compact to storage
- ⊙ Tripod is operable by pushing a lock-release button

### Product Specifications

|   |                              |
|---|------------------------------|
| <b>Color temperature</b>                          | 5000 K                       |
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b> | Li-ion                       |
| <b>Angle range horizontal</b>                     | 115 °                        |
| <b>Tool weight with battery (EPTA)</b>            | 7,4 - 8,1 kg                 |
| <b>Illuminance</b>                                | 1250 / 750 / 400 lx          |
| <b>Battery Voltage</b>                            | 14,4 / 18 V                  |
| <b>Product Dimensions (L x W x H):</b>            | 573 x 658 x 1 250 - 2 240 mm |
| <b>Voltage LXT</b>                                | 1                            |
| <b>System</b>                                     | LXT 18V/36V                  |
| <b>Product net weight (new)</b>                   | 7,4 kg                       |
| <b>Luminous flux</b>                              | 3000 / 1700 / 900 Lumen      |
| <b>Dimensions, foldable (L x W x H)</b>           | 260 x 216 x 1 000 mm         |
| <b>Angle range vertical</b>                       | 110 °                        |
| <b>Tool Category</b>                              | Lights                       |
| <b>International Protection Class (IP)</b>        | IP55                         |
| <b>Continuous use 18V / 5.0 Ah battery</b>        | 3 / 5,5 / 10 h               |

---

## Standard Equipment

- ⦿ Sold without Battery or Charger

## More info

<https://makita.ae/product/tower-light-work-light-lxt-dml814z/>