

Wheelbarrow LXT

DCU602Z



Product Description

36V (18Vx2) LXT • 180 kg • 0 - 1.5 / 3.5 / 5.0 km/h

4-wheel battery powered wheelbarrow powered by two 18V LXT® Li-Ion batteries in series. Equipped with a dump bucket which can be operated electronically or manually.

Increased max load capacity up to 300kg only on flat ground. Up to 4 batteries can be installed for long run time. Three forward speeds and one reverse, with variable speed control by switch trigger in each range

- Equipped with electric and electromagnetic brakes on top of hand lever-operated mechanical brake. Headlights, taillight, warning beeper and level gauge for more convenience. Swivel lock fixes the direction of rear tyres.

Product Specifications

Travelling speed reverse	0 - 1 km/h
Max climbing capacity	12 °
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	145 - 147 kg
Brushless Motor	YES
Battery Voltage	2 X 18 V
Sound Pressure Level	70 dB(A)
Travelling speed forward	0 - 1,5 / 3,5 / 5,0 km/h
Product Dimensions (L x W x H):	1480 x 730 x 820 - 1030 mm
Continuous use 18V / 6.0 Ah x4	100 min
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration Level (3 axes)	≤ 2,5 m/s ²
Max load capacity	180 kg
Voltage LXT	1
Product net weight (new)	144,3 kg
System	LXT 18V/36V
Noise Uncertainty (K Factor)	4 dB(A)
Tool Category	Transportation

Standard Equipment

- ⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/wheelbarrow-lxt-dcu602z/>